



0957



**B.V. Steenfabriek Huissenswaard**

**Postbus 48**

**NL-6690 AA Gendt**

**The Netherlands**

**2006**

**0957-CPD-0608**

**NEN-EN 771-1, April 2003, and NEN-EN 771-1/A1, March 2005**

**category I, HD clay bricks**

**Production code DCERP**

**DF Caprice Baccara - Exclusief Roodpaars**

**intended for**

Handmade facing bricks for interior and exterior use; for decorative or construction walls

<b>Length</b>	212 mm, T2 ( $\pm$ 4 mm), R1 (9 mm)
<b>Width</b>	101 mm, T2 ( $\pm$ 3 mm), R1 (6 mm)
<b>Thickness</b>	66 mm, T2 ( $\pm$ 2 mm), R1 (4 mm)
<b>Appearance</b>	Volle handvorm- of vormbaksteen eventueel met frog (<20% van het volume), Eurogroep 1
<b>Average compressive strength</b>	$\geq$ 15 N/mm <sup>2</sup>
<b>Dimensional stability</b>	NPD
<b>Bond strength</b>	0.15 N/mm <sup>2</sup> voor metselwerk en 0.30 N/mm <sup>2</sup> voor lijmwerk
<b>Active soluble salts</b>	S2
<b>Soluble sulphate</b>	$\leq$ 0,10 % m/md
<b>Reaction to fire</b>	Euroklasse A1
<b>Water absorption</b>	$\leq$ 14 % m/md
<b>Initial rate of water absorption</b>	IW4 Sterk zuigend, >4.0 kg/m <sup>2</sup> .min
<b>Water vapour diffusion coefficient</b>	5/10
<b>Gross dry density</b>	1780 kg/m <sup>3</sup> , D1 (10 %, $\pm$ 178 kg/m <sup>3</sup> )
<b>Thermal conductivity</b>	0,52 W/mK ( $\lambda$ 10, droog)
<b>Freeze/thaw resistance</b>	F2 Vorstklasse D (NBRL 1007)